

TagPlus-TH is a multiple-use temperature and humidity data logger with an LCD screen for easy viewing of temperature data. In this device, parameters can be configured by a professional user before use. Complete trip history is recorded and downloaded as encrypted reports with summary data, graphs, and tables, the report can be directly read by PC at the destination. And the temporary mode allows this Thermometer Hygrometer to continue working after users have generated and read the temporary report. It is an ideal choice for monitoring and recording the temperature and humidity changes of sensitive goods during transportation.

FEATURES

- Multi-use, configurable parameters
- Temporary reports available
- Up to 9 event markers
- Up to 6 alarm points
- Battery life up to 180 days, replaceable batteries
- $\pm 0.5^{\circ}\text{C}$ at full range (-30°C to $+70^{\circ}\text{C}$)
- 35,000 readings maximum memory capacity

APPLICATIONS

- Cold Chain Storage
- Data Center
- Hospitals & Restaurant
- Workspace, laboratories
- Residential space
- Office space environmental testing
- Agricultural greenhouses and breeding Laboratory



TECHNICAL SPEC

| | | | |
|---------------------|---|----------|---------------------------|
| Temperature Range | -30°C ~ +70°C | Accuracy | $\pm 0.5^{\circ}\text{C}$ |
| Humidity Range | 0~100%RH | Accuracy | $\pm 3\%RH$ |
| Resolution | 0.1°C, 0.1%RH | | |
| Storage Capacity | 35000 readings PDF only, 20000 readings PDF & CSV | | |
| Log Interval | 1 minute-24 hours | | |
| Protection Class | IP65 | | |
| Start mode | 0 minute-24 hours | | |
| Stop mode | Memory full; When into USB | | |
| Connection | USB, NFC (optional) | | |
| Storage Environment | $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$ (No battery) | | |
| File Format | PDF/CSV/PDF&CSV | | |
| Battery Type | 3.0V CR2032 lithium battery | | |
| Dimension | 82mm x 39mm x 13.5mm | | |
| Report Output | Automatic, no software needed | | |
| Weight | 30g | | |